

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 13

LOCTITE CAT 27-1 3kg

SDS No. : 373975 V004.0 Revision: 15.03.2023 printing date: 31.05.2023 Replaces version from: 23.05.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier LOCTITE CAT 27-1

LOCITIE CAT 27-1

1.2. Relevant identified uses of the substance or mixture and uses advised against Intended use: Epoxy Hardener

1.3. Details of the supplier of the safety data sheet

Henkel Ltd Adhesives Wood Lane End HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):	
Acute toxicity	Category 4
H302 Harmful if swallowed.	
Route of Exposure: Oral	
Acute toxicity	Category 4
H312 Harmful in contact with skin.	
Route of Exposure: Dermal	
Skin corrosion	Sub-category 1B
H314 Causes severe skin burns and eye damage.	
Serious eye damage	Category 1
H318 Causes serious eye damage.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Specific target organ toxicity - repeated exposure	Category 2
H373 May cause damage to organs through prolonged or repeated exposure.	
Acute hazards to the aquatic environment	Category 1
H400 Very toxic to aquatic life.	
Chronic hazards to the aquatic environment	Category 1
H410 Very toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:	
Contains	diethylmethylbenzenediamine
	2-Propanamine, compd. with boron trifluoride, reaction products with Bu glycidyl ether
Signal word:	Danger
Hazard statement:	 H302+H312 Harmful if swallowed or in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H373 May cause damage to organs through prolonged or repeated exposure. H410 Very toxic to aquatic life with long lasting effects.
D	P273 Avoid release to the environment.
Precautionary statement: Prevention	P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statement: Response	 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER or doctor.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
diethylmethylbenzenediamine 68479-98-1 270-877-4 01-2119486805-25	50- 100 %	Acute Tox. 4, Oral, H302 STOT RE 2, H373 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Acute Tox. 4, Dermal, H312	M acute = 1 M chronic = 1	
2-Propanamine, compd. with boron trifluoride, reaction products with Bu glycidyl ether 68478-97-7 270-846-5 01-2120762054-60	5- 10 %	Skin Corr. 1B, H314 Acute Tox. 4, Oral, H302 Skin Sens. 1B, H317 Aquatic Chronic 1, H410 Eye Dam. 1, H318	M chronic = 1	

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation: Move to fresh air.

Skin contact: IF ON SKIN: Wash with plenty of soap and water. Seek medical advice.

Eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Seek medical advice.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed SKIN: Redness, inflammation.

INGESTION: Nausea, vomiting, diarrhea, abdominal pain.

After eye contact: Corrosive, may cause permanent damage to eyes (impairment of vision).

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media Suitable extinguishing media: water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons: High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released. carbon oxides.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Wear protective equipment. Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal. Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact. See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed. Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction. Keep container tightly sealed. Refer to Technical Data Sheet

7.3. Specific end use(s) Epoxy Hardener

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

None

Occupational Exposure Limits

Valid for

Ireland

None

Predicted No-Effect Concentration (PNEC):

Name on list Environmental Exposure Value							Remarks
	Compartment	period	mg/l	ppm	mg/kg	others	
Diethylmethylbenzenediamine 68479-98-1	aqua (freshwater)		0,001 mg/l				
Diethylmethylbenzenediamine 68479-98-1	sediment (freshwater)				0,029 mg/kg		
Diethylmethylbenzenediamine 68479-98-1	aqua (marine water)		0,0001 mg/l				
Diethylmethylbenzenediamine 68479-98-1	sediment (marine water)				0,0029 mg/kg		
Diethylmethylbenzenediamine 68479-98-1	Soil				0,0056 mg/kg		
Diethylmethylbenzenediamine 68479-98-1	sewage treatment plant (STP)		17 mg/l				
Diethylmethylbenzenediamine 68479-98-1	aqua (intermittent releases)		0,005 mg/l				
Diethylmethylbenzenediamine 68479-98-1	oral				2 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Diethylmethylbenzenediamine 68479-98-1	Workers	inhalation	Long term exposure - systemic effects		0,13 mg/m3	
Diethylmethylbenzenediamine 68479-98-1	Workers	dermal	Long term exposure - systemic effects		1 mg/kg	
Diethylmethylbenzenediamine 68479-98-1	General population	oral	Long term exposure - systemic effects		0,1 mg/kg	
Diethylmethylbenzenediamine 68479-98-1	General population	dermal	Long term exposure - systemic effects		1 mg/kg	
Diethylmethylbenzenediamine 68479-98-1	General population	inhalation	Long term exposure - systemic effects		0,1 mg/m3	

Biological Exposure Indices: None

8.2. Exposure controls:

Engineering controls: Ensure good ventilation/extraction.

Respiratory protection: Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection: Wear suitable protective clothing. Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

<i>.</i>	mor mation on basic physical and chemical properties	cs
	Delivery form	Currently under determination
	Colour	Brown
	Odor	amine-like
	Physical state	liquid
	Melting point	-32 °C (-25.6 °F)
	Initial boiling point	> 200 °C (> 392 °F)
	Flammability	Currently under determination
	Explosive limits	Currently under determination
	Flash point	>100 °C (>212 °F)
	Auto-ignition temperature	Currently under determination
	Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic
		peroxide and does not decompose under foreseen conditions of use
	pH	Currently under determination
	Viscosity (kinematic)	Currently under determination
	Solubility (qualitative)	Currently under determination
	Partition coefficient: n-octanol/water	Not applicable
		Mixture
	Vapour pressure	Not applicable
	Density	1,02 g/cm3 None

() Relative vapour density:

Particle characteristics

Not available. Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity Strong oxidizing agents. Strong bases. Acids.

10.2. Chemical stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid No decomposition if stored and applied as directed.

10.5. Incompatible materials See section reactivity.

10.6. Hazardous decomposition products

Hydrocarbons carbon oxides. nitrogen oxides Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
diethylmethylbenzenedia mine 68479-98-1	LD50	738 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
2-Propanamine, compd. with boron trifluoride, reaction products with Bu glycidyl ether 68478-97-7	LD50	730 mg/kg	rat	not specified

Acute dermal toxicity:

No substance data available. No data available.

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
diethylmethylbenzenedia	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
mine				
68479-98-1				
2-Propanamine, compd. with boron trifluoride, reaction products with Bu	corrosive		rabbit	other guideline:
glycidyl ether 68478-97-7				

Serious eye damage/irritation:

No data available.

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
2-Propanamine, compd. with boron trifluoride, reaction products with Bu glycidyl ether 68478-97-7	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Type of study /	Metabolic	Species	Method
CAS-No.		Route of	activation /		
		administration	Exposure time		

Carcinogenicity

No data available.

Reproductive toxicity:

No data available.

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of	Species	Method
		upphention	treatment		
diethylmethylbenzenedia mine 68479-98-1	NOAEL 8 mg/kg	oral: feed	90 days daily	rat	EU Method B.26 (Sub- Chronic Oral Toxicity Test: Repeated Dose 90- Day Oral Toxicity Study in Rodents)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
diethylmethylbenzenediamine	LC50	> 106 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish,
68479-98-1					Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
diethylmethylbenzenediamine	EC50	0,5 mg/l	48 h	Daphnia magna	OECD Guideline 202
68479-98-1					(Daphnia sp. Acute
					Immobilisation Test)
2-Propanamine, compd. with	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202
boron trifluoride, reaction					(Daphnia sp. Acute
products with Bu glycidyl					Immobilisation Test)
ether					
68478-97-7					

Chronic toxicity (aquatic invertebrates):

No data available.

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_		
2-Propanamine, compd. with boron trifluoride, reaction products with Bu glycidyl ether 68478-97-7	EC50	> 1,3 - < 2 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Propanamine, compd. with boron trifluoride, reaction products with Bu glycidyl ether 68478-97-7	NOEC	0,1 mg/1	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
diethylmethylbenzenediamine 68479-98-1	EC10	170 mg/l	24 h		not specified

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
diethylmethylbenzenediamine 68479-98-1		aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
2-Propanamine, compd. with boron trifluoride, reaction products with Bu glycidyl ether 68478-97-7	not readily biodegradable.	aerobic	27 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

Cured adhesives are immobile.

No substance data available.

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	PBT / vPvB
CAS-No.	
diethylmethylbenzenediamine	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
68479-98-1	Bioaccumulative (vPvB) criteria.
2-Propanamine, compd. with boron trifluoride,	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
reaction products with Bu glycidyl ether	Bioaccumulative (vPvB) criteria.
68478-97-7	

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water. Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

ADR	2735
RID	2735
ADN	2735
IMDG	2735
IATA	2735
IAIA	2155

14.2. UN proper shipping name

ADR	AMINES, LIQUID, CORROSIVE, N.O.S. (Boron (2-propanamine) trifluoro-
	butylglycidylether reaction product)
RID	AMINES, LIQUID, CORROSIVE, N.O.S. (Boron (2-propanamine) trifluoro-
	butylglycidylether reaction product)
ADN	AMINES, LIQUID, CORROSIVE, N.O.S. (Boron (2-propanamine) trifluoro-
	butylglycidylether reaction product)
IMDG	AMINES, LIQUID, CORROSIVE, N.O.S. (Boron (2-propanamine) trifluoro-
	butylglycidylether reaction product, Diethyltoluene diamine)
IATA	Amines, liquid, corrosive, n.o.s. (Boron (2-propanamine) trifluoro-butylglycidylether
	reaction product)

14.3. Transport hazard class(es)

ADR	8
RID	8
ADN	8
IMDG	8
IATA	8

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable
	Tunnelcode: (E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

< 3 %

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):

Persistent organic pollutants (Regulation (EU) 2019/1021):

VOC content (2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very
	bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.

Not applicable Not applicable Not applicable